



MODEL 2300 Dryer Systems

features

- PVC and Titanium Body Construction
- Internal Electric Enclosure
- Self Contained Air Turbine
- Clear Top Cover
- Conveniently Located Controls
- Utilizes Chemcut AFD™ Technology
- Digital Conveyor Speed Display


Available Options

- Choose From 5 Conveyor Widths
15 to 60 Inch(381 to 1524mm)
- Ultrathin™ Thin Panel Conveyor
- Flextrak™ Thin or Flex Panel Conveyor
- Single, Dual or Triple Chemcut AFD™
- Casters to allow portability
- 190 to 480 volt 50/60 Hz Power Choices

Overview

Chemcut's new line of dryer systems offers a wide range of flexibility for all drying needs. These dryers can be configured as portable units that can be moved around within production shops. Or, they may be permanently installed at critical need shop locations.

The dual and triple Chemcut AFD™ options dry the most difficult high aspect panels up to 0.250 inch (6.4 mm) thick. The exclusive Flextrak™ option can flawlessly dry thin panels down to 0.001 inches(25 micron).



CHEMCUT CORPORATION

500 Science Park Road • State College, PA 16803
1-800-CHEMCUT (1-800-243-6288) • Tel: 814-272-2800 • Fax: 814-272-5205
email: bluebox@chemcut.net • www.chemcut.net